

● PRINTER RUSH ●

(PTO ASSISTANCE)

Application : 10/017938 Examiner : Maust GAU : 3751
 From : NAB Location : IDC FMF FDC Date : 10/28/05

Tracking #: epm 10617938 Week Date: 10-17-2005

DOC CODE	DOC DATE	MISCELLANEOUS
<input type="checkbox"/> 1449	_____	<input type="checkbox"/> Continuing Data
<input type="checkbox"/> IDS	_____	<input type="checkbox"/> Foreign Priority
<input type="checkbox"/> CLM	_____	<input type="checkbox"/> Document Legibility
<input type="checkbox"/> IIFW	_____	<input type="checkbox"/> Fees
<input type="checkbox"/> SRFW	_____	<input type="checkbox"/> Other
<input checked="" type="checkbox"/> DRW	<u>—</u>	
<input type="checkbox"/> OATH	_____	
<input type="checkbox"/> 312	_____	
<input checked="" type="checkbox"/> SPEC	<u>7-11-2003</u>	

[RUSH] MESSAGE: _____

Drawing Figures 1 and 2 are missing.
as described in the specification. Please either
mail a Notice of Allowability requiring drawings or
delete references to drawings from specification

Thank You
NAB

ICAT

[XRUSH] RESPONSE: _____

INITIALS:

NOTE: This form will be included as part of the official USPTO record, with the Response document coded as XRUSH.

REV 10/04

illustrate only some embodiments of the invention and are therefore not to be considered limiting of its scope, because the invention may admit to other equally effective embodiments.

5 [0052] Figure 1 is a functional block diagram of a system comprising a diluent source and a plurality of concentrate sources, each being in fluid communication with a common mixing chamber; and

[0053] Figure 2 is a functional block diagram of a system
10 comprising a diluent source and a plurality of concentrate sources, each being in fluid communication with a plurality of mixing chambers.

DETAILED DESCRIPTION OF THE INVENTION

[0054] Referring to Figure 1, a machine 1a comprises a
15 diluent source 1, for example water, and a plurality of concentrate sources 2 to 5. Said diluent and concentrate sources are in fluid communication with a mixing chamber 6 through a series of conduits 7 to 11, respectively controlled by control valves 12 to 16. Said control valves
20 12 to 16 may be automatically or manually operated. Said mixing chamber 6 in fluid communication with a dispense point 17, which is controlled by a control valve 18, said dispense point 17 serving to dispense product to a storage container 19, which may be an integral component of the
25 machine, or in an alternative embodiment, may be external to